

EV Charging Cable - Type 2 Female to Type 2 Male 32A

A 32A single phase charging cable for use on any BEV (Battery Electric Vehicle) and PHEV (Plug-in Hybrid Electric Vehicle) that uses a Type 2 connector. Suitable for use with 220/230V home wall box chargers, but can also be used in public charge points, with a maximum power output 7.4kW. Supplied in a zip-up carry-case so that it can be kept safely and tidily in the vehicle when not in use.



Additional Information

- 10m long BEV/PHEV charging cable, with Type 2 vehicle plug (female) to Type 2 charger plug (male), complete with carry bag.
- Single phase voltage up to 220/230V AC, for charging at up to 7.4kW.
- Tested to 2,500V DC. Operating temperature: -30C to +50C. Connectors made from durable polycarbonate with copper alloy contacts.
- Applications include: Audi, BMW, Hyundai, Jaguar, Kia, Lucid Air, Mercedes, MINI, Nissan Leaf (2018), Porsche, Range Rover P400e, Renault, Smart, Tesla, Toyota, Volkswagen, Volvo.
- IP55 rated, IEC, UL, TUV, CE & UKCA compliant. 5m length charging cable also available, please see Part No. 8620.

<http://lasertools.co.uk/product/8621>

Video available: <https://youtu.be/UwVeadjYgV4>



Type 2 Female to Type 2 Male

