

EV Charging Cable - 32A Three Phase T2 Female-T2 Male

A 32A three phase charging cable for use on any BEV (Battery Electric Vehicle) and PHEV (Plug-in Hybrid Electric Vehicle) that uses a Type 2 connector. Suitable for use with 415V public charge points, with a maximum power output 22kW. Supplied in a zip-up carry-case so that it can be kept safely and tidily in the vehicle when not in use. Please note: Three phase cables can also be used on single phase charge points, but not vice-versa.



Additional Information

- 5m long BEV/PHEV charging cable, with Type 2 vehicle plug (female) to Type 2 charger plug (male), complete with carry bag.
- Three phase voltage up to 415V AC, for rapid charging up to 22kW.
- Tested to 2,000V AC. Operating temperature: -20C to +50C. Connectors made from durable polycarbonate with copper alloy contacts.
- Applications include: Audi, BMW, BYD, Ford, Hyundai, Jaguar, Kia, Lucid Air, Mercedes-Benz, MINI, Nissan Leaf (2018), Polestar, Porsche, Range Rover P400e, Renault, Smart, Tesla, Toyota, Volkswagen & Volvo.
- IP65 rated, IEC, TUV, CE & UKCA, REACH, RoHS compliant. EN62196, IEC61851.

<http://lasertools.co.uk/product/9106>

