

LASER[®]

Brake Bleed Bottle

Complete with 3 adaptors for most vehicles
A simple kit used to bleed brakes.

- Avoid contact with painted surfaces, clothing, skin and eyes.
 - Always wear eye protection.
 - Follow manufacturer's procedure order before bleeding brake lines.
 - If you jack up the vehicle, be sure to use jack stands.
1. Fill master cylinder with new brake fluid and keep it full during bleeding operation.
 2. Assemble bleed kit with short hose attached inside lid.
 3. Remove bleed screw from wheel cylinder and clean.
 4. Check the three adaptor connectors included and select one that best fits the bleed nipple.
 5. Replace bleed screw finger tight, then unscrew 1-2 turns and connect to adaptor.
 6. Pump brake pedal slowly, then check hose for air bubbles.
 7. Continue until there are no bubbles in hose.
 8. Remove Bleed kit and firmly tighten bleed nipple.
 9. Repeat procedure for remaining wheels.

Warning: Brake fluid is corrosive



Safety First. Be Protected.

- NL** REMONTLUCHTINGSSET
- F** KIT DE PURGE DE FRIEN
- DE** BREMSENTLUFTÜNGSSATZ
- IT** KIT PER PERDITE FRENI
- ES** KIT DE DRANJE DE FRENOS



Guarantee

If this product fails through faulty materials or workmanship, contact our service department direct on: **+44 (0) 1926 818186**. Normal wear & tear are excluded as are consumable items & abuse.