

Our products are designed to be used correctly and with care for the purpose for which they are intended. No liability is accepted by the Tool Connection for incorrect use of any of our products, and the Tool Connection cannot be held responsible for any damage to personnel, property or equipment when using the tools. Incorrect use will also invalidate the warranty.

If applicable, the applications database and any instructional information provided has been designed to offer general guidance for a particular tool's use and while all attention is given to the accuracy of the data no project should be attempted without referring first to the manufacturer's technical documentation (workshop or instruction manual) or the use of a recognised authority such as Autodata.

It is our policy to continually improve our products and thus we reserve the right to alter specifications and components without prior notice. It is the responsibility of the user to ensure the suitability of the tools and information prior to their use.



Safety First. Be Protected.



Guarantee

If this product fails through faulty materials or workmanship, contact our service department direct on: **+44 (0) 1926 818186**. Normal wear and tear are excluded as are consumable items and abuse.



Distributed by **The Tool Connection Ltd**

Kineton Road, Southam, Warwickshire CV47 0DR
T +44 (0) 1926 815000 **F** +44 (0) 1926 815888
info@toolconnection.co.uk www.toolconnection.co.uk

5843

LASER[®]

Diesel Fuel Filter Removal Kit

Vauxhall | Saab | Suzuki | Fiat | Citroën

Instructions



www.lasertools.co.uk

Diesel Fuel Filter Removal Kit

The Diesel Fuel Filter Removal kit has been developed to assist the removal and replacement of the filter element without risk of damaging the filter plastic body.

These filter housings are not disposable and the filter is supplied as an element only.

The two piece kit provides a vice stand for the filter outer body to be held securely and an adaptor which fits snugly onto the top of the filter housing to allow a 1/2"D wrench to be used to separate the top of the filter housing from the body.

Applications: Chevrolet, Citroën, Fiat, Saab, Suzuki, Vauxhall

Engines Code:

1.3/JTD/CDTi/DDiS, 1.9/JTD/CDTi/TiD, 2.0/VCDi/HDi/JTD,
2.2/JTD/HDi, 2.8/JTD/HDi, 3.0/JTD/HDi



Removal Adaptor



Filter Body Stand

Instructions for use

- Remove the filter body completely from the vehicle
- Mount the filter housing body as shown in the filter body stand and place in a suitable vice, do not over tighten the vice.
- Place the removal adaptor on the top of the filter housing and loosen.
- Remove the internal filter element, clean the internals of the filter housing and insert new filter.
- Fit new filter housing seal and ensure correct alignment then tighten filter housing to recommended torque.

