### 20V 4.0AH **'ONE BATTERY POWERS ALL'** LI-ION BATTERY



Features 10 lithium cells, diagnostic LED to read health plus built in protection against over heating and overcharging.

- Protection against over heating & overcharging with a built in cooling channel which operates during the charging process.
- · LED power gauge lights to determine the remaining battery power.
- 4.0Ah battery with 10 lithium cells. Average charge time (to full charge): 60mins.

#### **SPECIFICATIONS**

Voltage	20v DC
Capacity	4.0Ah
Rechargeable Cells	10 x Li-lon
Cell type	Cylindrical ICR18650
Nominal Voltage per Cell	3.7v
Max /Min Voltage per Cell	4.2v (charge) - 2.75v (discharge)
Charge time (empty to full) @ 4A	60 mins
Safety features	Shortcircuit protection, over heating protection, over charging protection













### **Full Laser Tools Cordless Powertool Range Available**









## **230V MAINS 4 AMP**

# **BATTERY CHARGER**



PAST • PRESENT • FUTURE



Mains battery charger is used with the 10 cell lithium battery (Part No. 8007).

- 230V mains input 12V DC output, 4 amp with BS plug.
- LED diagnosis light to determine the state of battery health.
- · Protection against over heating and overcharging.

### **SPECIFICATIONS**

N YAYYA I KA	
Input Voltage	230v
Output Voltage	20V DC
Charge Current	4 amp
Charge time (from empty)	60 mins
Battery Usage time (depending on tool & usage)	40 - 115 mins













8013

CORDLESS IMPACT

WRENCH



**Full Laser Tools Cordless Powertool Range Available** 









## **CORDLESS** ANGLE GRINDER



NEW Comfort soft grip design with all metal gears and brushless motor technology built for daily use. Includes disc locking tool. FOR ALI ONE LASER **POWERTOOLS** 20V No Load Speed



- 8000min<sup>-1</sup> adjust the gear according to different working conditions.
- Fits up to 115mm cutting and grinding discs and features an easy to adjust guard for multiple angle applications.





### Additional Features:

• Comfort grip with optional locking switch. M14 spindle with spindle lock function for ease of disc changeover.









### **SPECIFICATIONS**

(a, b) = (a, b)	
Battery	20V-4Ah
Max no load speed (RPM)	8000
Speed Switch	Lockable switch
Dia Wheel	115mm (4 - 1/2")
Overall dimensions (mm) with battery	385 x 230 x 130
Weight (kg)	1.6 (no battery) - 2.2 (with battery)
Noise (dB)	85-130
Extra Features	Dust screen, interchangeable handle, spindle lock, aluminium gear box
Safety Features	Trigger switch lock & motor overload protection









For more information or to order:

Tel: +44 1926 815000 Email: sales@toolconnection.co.uk